

# TORQUE WRENCHES

## HYDRAULIC TORQUE WRENCH

### ▼ BBT SERIES

- Safety mechanism with reverse rotation protection.
- 360° rotating reaction arm for optimal positioning.
- Push-button square drive for quick direction change.



Model No.	Square Drive (inch)	Torque (N.m)	Weight (kg)
0.7BBT	3/4"	107~1,110	1.8
1BBT	3/4"	176~1,830	2.5
3BBT	1"	450~4,510	5.0
5BBT	1-1/2"	745~8,520	8.0
8BBT	1-1/2"	1,068~10,770	11.0
10BBT	1-1/2"	1,550~15,510	15.0
20BBT	2-1/2"	2,657~26,660	26.5
25BBT	2-1/2"	3,470~34,725	35.0
35BBT	2-1/2"	4,860~48,670	50.0
50BBT	2-1/2"	7,198~72,000	87.0

### ▼ BBC SERIES

- Compact design for access in narrow spaces.
- Built-in reverse rotation prevention mechanism.
- Wide bolt coverage through interchangeable sleeve sizes.



Model No.	Nut Size (mm)	Torque (N.m)	Head Weight (Kg)	Link Weight (Kg)
2BBC	19~60	215~2,380	0.9	1.5
4BBC	34~80	550~6,108	1.6	3.4
8BBC	41~105	1,040~11,230	3.0	6.3
14BBC	50~117	1,810~18,520	4.8	11.4
30BBC	85~175	4,190~44,590	10.5	20.5

## HYDRAULIC PUMP

Pressure	700bar / 10,000psi
Voltage	220V/60Hz
Power	1.1kW
Tank Capacity	5.5L
Weight	23Kg
LxWxH	419x295x464mm

### ▼ BP3

- Compact design for easy handling.
- Multiple torque wrenches can be connected simultaneously (optional).
- Oil cooler installed for duty operation.
- Pressure adjustable from 0 to 10,000 psi.

