

PNEUMATIC ROLLING DRIVES

50 SERIES



▼ FEATURES

- Lightweight aluminum body.
- User-friendly push/pull throttle.
- Stops tube expansion at the set value.
- Provides precise control of torque output.

50-400		Torque		Tube Capacity		Free Speed		Air Consumption	
		Min. 5.0Nm Max. 36.0Nm		Max. O.D.31.75mm (1-1/4")		400RPM		1,700 liter/min	
Coupling No.	33, 34	Square Drive	9.5mm (0.37")	Overall Length	311mm (12-1/4")	Weight	4.8kg		

72 SERIES



▼ FEATURES

- Unique head design developed for heavy-duty applications.
- Easily adjustable torque.
- Angle head adjustable in multiple positions.
- 360° adjustable air exhaust.

72-RT-190		Torque		Tube Capacity		Free Speed		Air Consumption	
		Min. 95Nm Max. 190Nm		Max. O.D.63.5mm (2.5")		190RPM		1,982 liter/min	
Square Drive	15.88mm (5/8")	Overall Length	530mm (21")	Weight	5.8kg				

72-RT-90		Torque		Tube Capacity		Free Speed		Air Consumption	
		Min. 200Nm Max. 410Nm		Max. O.D.101.6mm (4")		90RPM		1,982 liter/min	
Square Drive	19.05mm (3/4")	Overall Length	530mm (21")	Weight	6.7kg				